



Operating Radius (m)	Total Rated Loads - Main Boom										
	Outriggers fully extended										
	Front jack extended (360°) / Front jack not extended (over sides and rear)										
	15.50m	21.20m	26.80m	32.50m	38.10m	43.80m	49.40m	55.10m	60.70m	66.40m	72.00m
2.50	220.0										
3.00	175.0	133.0									
4.00	134.0	125.0	90.0								
5.00	117.0	111.0	90.0	68.0							
6.00	104.0	100.0	90.0	68.0	52.0						
7.00	92.5	89.5	86.0	68.0	52.0	40.0					
8.00	83.0	81.5	78.5	68.0	52.0	40.0	30.0				
9.00	74.5	74.5	71.5	65.5	52.0	40.0	30.0	23.5			
10.00	66.0	68.5	65.5	62.0	52.0	40.0	30.0	23.5			
11.00	57.4	61.0	59.5	59.0	50.5	40.0	30.0	23.5	18.0		
12.00	47.5	54.5	53.0	54.0	48.5	38.5	30.0	23.5	18.0	14.0	
13.00		49.5	48.0	49.0	46.0	37.0	29.0	23.5	18.0	14.0	
14.00		45.0	43.5	44.5	44.0	36.0	28.0	23.0	18.0	14.0	12.0
15.00		41.0	39.5	40.5	41.5	34.5	26.5	22.0	18.0	14.0	12.0
16.00		38.0	36.5	37.0	38.0	33.0	25.5	20.5	18.0	14.0	12.0
18.00		26.5	31.0	32.5	32.5	31.0	23.5	18.8	17.9	14.0	12.0
20.00			26.5	29.0	28.5	29.0	21.5	17.4	16.8	14.0	12.0
22.00			23.0	25.5	25.0	26.0	19.9	16.1	15.7	13.8	12.0
24.00				22.5	22.5	23.0	18.1	14.7	14.7	13.4	11.9
26.00				20.0	21.0	20.5	16.4	13.6	13.6	12.7	11.5
28.00				17.4	19.1	18.3	15.2	12.5	12.6	11.9	11.1
30.00					17.3	16.5	14.2	11.4	11.7	11.1	10.6
32.00					15.7	14.8	13.5	10.4	10.8	10.3	9.8
34.00					12.7	13.2	12.9	9.3	10.0	9.6	9.1
36.00						11.9	12.2	8.6	9.1	8.8	8.3
38.00						10.7	11.6	8.2	8.3	8.0	7.8
40.00						9.3	10.5	7.9	7.4	7.2	7.2
42.00							9.6	7.6	7.0	6.8	6.8
44.00							8.7	7.3	6.5	6.4	6.4
46.00							6.5	7.0	6.1	6.0	6.0
48.00								6.7	5.8	5.6	5.5
50.00									5.5	5.2	5.1
52.00									5.3	5.0	4.8
54.00									5.1	4.7	4.5
56.00									4.8	4.4	4.2
58.00										4.2	3.9
60.00										3.9	3.6
62.00										2.9	3.2
64.00											2.9
66.00											2.5

